

# Hydrotex® Engine Oil Quick Reference Guide



Engine Oil	SKU	SAE Viscosity	Engine Types			Approvals	Recommended for:	Description
			Diesel	Gasoline	Natural Gas			
<b>HyFilm® LEO Heavy Duty</b>	0012	5W-40	✓	✓		API CK-4/SN, Volvo VDS-4.5, Mack EOS-4.5, Renault VI RLD-3	CES 20086, DDC 93K222, CAT ECF-3, MB 228.51, MB 228.31, Ford WSS-M2C171-E, JASO DH-2, ACEA E9	HyFilm LEO Heavy Duty offers premium, comprehensive protection for medium- and heavy-duty diesel engines while extending drain intervals, optimizing fuel economy and reducing emissions. It is backward compatible with legacy engines. SAE 5W-40 and 5W-30 formulations exceed API CK-4/SN requirements for use in mixed gasoline & diesel fleets.
		5W-30	✓	✓		API CK-4/SN, Volvo VDS-4.5, Mack EOS-4.5, Renault VI RLD-3, DDC 93K222	CES 20086, CAT ECF-3, MB 228.31, Ford WSS-M2C171-E, JASO DH-2, ACEA E9	
		15W-40	✓			API CK-4, Volvo VDS-4.5, Mack EOS-4.5, Ford WSS-M2C171-F1, Renault VI RLD-4	CES 20086, DDC 93K222, CAT ECF-3, MB 228.31, JASO DH-2, ACEA E9	
		10W-30	✓					
<b>HyFilm FST</b>	0032	10W-30	✓			API FA-4, DDC 93K223	CES 20087	HyFilm FST is a premium performance diesel engine oil featuring "Fuel Saving Technology," which provides outstanding wear protection and long oil life with tightly controlled high temperature viscosity characteristics for increased fuel economy. For use only in on-road diesel engines specifying API FA-4 engine oil.
<b>HyFilm LEO EPG</b>	0018	5W-30		✓	✓	API Starburst, API SN Resource Conserving, ILSAC GF-5	GM dexos1, Chrysler MS-6395T, Ford WSS-M2C946-A	HyFilm LEO EPG protects gasoline engines while maximizing fuel economy and extending service intervals. Designed to meet the rigorous demands of modern high output turbocharged and supercharged gasoline engines, HyFilm LEO EPG is compatible with legacy gasoline engines.
		5W-20		✓	✓		GM dexos1, Chrysler MS-6395T, Ford WSS-M2C945-A	
<b>HyFilm LEO EPD</b>	0019	5W-30	✓	✓			ACEA C3-16, MB 229.51, Chrysler MS-11106, VW 504.00, VW 507.00, Porsche C30, BMW LL 04, API SN	HyFilm LEO EPD exceeds the requirements of key European light-duty diesel and high performance gasoline engine manufacturers.
<b>HyFilm Majestic™ Engine Oil</b>	0312	15W-40	✓			API CK-4	CES 20086, DDC 93K222, CAT ECF-3, MB 228.31, JASO DH-2, ACEA E9	HyFilm Majestic high performance engine oils offer superior wear protection, soot dispersancy and viscosity control for engines prone to high levels of contamination, fuel dilution or leakage. Note: Available only in bulk with prior approval.
		5W-30		✓	✓	API Starburst, API SN Resource Conserving, ILSAC GF-5	GM dexos1, Chrysler MS-6395T, Ford WSS-M2C946-A	
<b>HyFilm LEO G92</b>	1292	15W-40			✓		CES 20092, DDC 93K216, Volvo CNG MB 226.9, Renault RGD	HyFilm LEO G92 provides specialized protection for modern stoichiometric-burn natural gas engines from Cummins-Westport, Detroit Diesel, Volvo and others. HyFilm LEO G92 ensures long engine life and protection from valve recession, valve torching, piston scuffing and spark plug fouling, while extending drain intervals and reducing oil consumption.
<b>HyFilm LEO G74</b>	1274	15W-40			✓		CES 20074, DDC 93K216, Allison C-4	HyFilm LEO G74 provides specialized protection for legacy lean-burn natural gas engines from Cummins-Westport, Detroit Diesel, ISUZU and others.
<b>HyFilm NG</b>	0011	15W-40			✓		Waukesha, GE, Dresser, Jenbacher, Caterpillar, Clark, Wartsila, Cooper-Bessemer, Fairbanks-Morse	HyFilm NG is a high performance low-ash natural gas engine oil for use in stationary engines, firewater engines, and generators. It protects against valve recession, valve torching, piston scuffing and spark plug fouling, while extending drains and reducing oil consumption.
		40			✓			
<b>Team Racing Motor Oil</b>	0052	15W-50		✓			Racing Engines, Flat Tappet Applications, High Temperature & Shear Applications	The winning combination of performance and durability, Team Racing Motor Oil features extreme anti-wear protection and stability for the extreme operating conditions of high-output engines used in drag racing, track racing and off-road racing. Not recommended for on-road use.
<b>HyFilm Hy-Rev</b>	0058	N/A		✓			API TC, SAETC, ISO EGD, JASO FC, JASO FD	HyFilm Hy-Rev is a low ash, high performance oil for air-cooled, 2-cycle gasoline engines. It protects against scuffing, wear, and spark plug fouling, and keeps combustion chambers clean. For use in chainsaws, lawnmowers, weed eaters, and select ATV models.

OEM names and trademarks are property of their respective owners and their use does not imply endorsement. Hydrotex name, design and related marks are trademarks of Hydrotex® 2020. Hydrotex all rights reserved.